

C-1-08							
	23.1	24.4	1.3		0.003	0.06	
	24.4	24.5	0.1		0.067	1.34	
	24.5	25.8	1.3		0.009	0.18	
	41.6	42.1	0.5		0.025	0.50	
					0.005	0.10	
					0.005	0.10	
					0.005	0.10	
	46.6	47.1	0.5		0.005	0.10	
	47.1	47.8	0.7		0.008	0.16	
	47.8	48.5	0.7		0.004	0.08	
	48.5	49.4	0.9		0.007	0.14	
	49.4	49.8	0.4		0.009	0.18	
	49.8	50.3	0.5		0.004	0.08	
	67.9	68.2	0.3		0.012	0.24	
	79.75	80.0	0.25		0.009	0.18	
	80.0	80.4	0.4		0.009	0.18	
	88.5	89.5	1.0		0.002	0.04	
	89.5	89.6	0.1		0.014	0.28	
	93.5	94.0	0.5		0.001	0.02	
	94.0	94.5	0.5		0.002	0.04	
	94.5	94.8	0.3		0.002	0.04	
	94.8	95.2	0.4		0.001	0.02	
	95.2	95.5	0.3		0.001	0.02	
	95.5	96.0	0.5		0.001	0.02	
	100.4	100.7	0.3		0.014	0.28	
	100.7	101.7	1.0		0.002	0.04	

C-2-08							
	9.7	9.9	0.2		0.008	0.16	
	28.0	28.6	0.6		0.008	0.16	
	28.6	29.1	0.5		0.003	0.06	
	29.1	29.6	0.5		0.002	0.04	
	29.6	30.3	0.7		0.001	0.02	
	30.3	30.8	0.5		0.002	0.04	
	30.8	31.3	0.5		0.002	0.04	
	31.3	31.8	0.5		0.004	0.08	
	31.8	32.3	0.5		0.001	0.02	
	32.3	32.6	0.3		0.001	0.02	
	37.4	37.65	0.25		0.007	0.14	
	46.2	47.3	1.1		0.001	0.02	
	47.3	47.7	0.4		0.019	0.38	
	47.7	48.0	0.3		0.006	0.12	
	48.0	48.4	0.4		0.006	0.12	
	56.7	57.0	0.3		0.007	0.14	
	57.0	57.7	0.7		0.006	0.14	
	65.0	65.3	0.3		0.006	0.12	
	65.3	66.0	0.7		0.012	0.24	
	73.4	73.5	0.1		0.003	0.06	

C-3-08							
	14.0	14.5	0.5		0.003	0.06	
	14.5	15.0	0.5		0.002	0.04	
	15.0	15.5	0.5		0.002	0.04	
	16.4	16.6	0.2		0.006	0.12	
	19.6	19.7	0.1		0.003	0.06	
	20.8	21.1	0.3		0.007	0.17	
	21.1	21.7	0.6		0.006	0.12	
	21.7	22.2	0.5		0.002	0.04	
	22.2	22.7	0.5		0.002	0.04	
	22.7	22.9	0.2		0.004	0.08	
	23.5	23.8	0.3		0.008	0.16	
	23.8	24.1	0.3		0.015	0.30	
	24.1	24.4	0.3		0.010	0.20	
	35.4	35.65	0.25		0.009	0.18	
	46.5	46.6	0.1		0.007	0.14	
	62.9	63.9	1.0		0.004	0.08	
	63.9	64.2	0.3		0.016	0.32	
	64.2	65.7	1.4		0.003	0.06	
	74.2	74.5	0.3		0.002	0.04	
	80.4	80.6	0.2		Trace		

Section A - from 23.5 m to 24.4 = 0.9 m

Average grade over 0.9 m = 0.011% U3O8 (0.22 lbs/ton)

C-4-08							
	60.0	60.5	0.5		0.002	0.04	
	60.5	61.0	0.5		0.004	0.08	
	61.0	61.5	0.5		0.002	0.04	
	61.5	62.0	0.5		0.003	0.06	
	62.0	62.5	0.5		0.002	0.04	
	62.5	63.0	0.5		0.001	0.02	
	63.6	64.05	1.45		0.002	0.04	
	64.05	64.5	0.45		0.002	0.04	
	66.3	66.75	0.45		0.004	0.08	
	66.75	67.13	0.43		0.003	0.06	
	67.13	67.6	0.44		0.002	0.04	
	76.7	76.8	0.1		0.003	0.06	
	80.3	80.4	0.1		0.002	0.04	
	91.1	91.2	0.1		0.003	0.06	
	100.7	101.0	0.3		0.010	0.20	
	101.0	101.3	0.3		0.026	0.52	
	101.3	102.5	1.2		0.004	0.08	
	102.5	102.7	0.2		0.051	1.02	
	102.7	104.0	1.3		0.002	0.04	
	104.0	104.15	0.15		0.001	0.02	
	104.15	104.4	0.25		0.012	0.24	
	104.4	105.5	1.1		0.003	0.06	
	105.5	105.7	0.2		0.002	0.04	
	109.0	109.1	0.1		0.008	0.16	
	110.3	110.6	0.3		0.001	0.02	
	112.4	112.6	0.2		0.003	0.06	
	112.6	113.3	0.7		0.006	0.12	
	113.75	114.05	0.3		0.004	0.08	
	116.7	117.0	0.3		0.001	0.02	
	120.1	120.3	0.2		0.003	0.06	
	121.2	121.4	0.1		0.002	0.04	
	126.9	127.0	0.1		Tr.	---	
	136.5	136.8	0.3		0.006	0.12	

C-5-08	42.0	42.2	0.2		Tr.	---	
	53.25	53.4	0.15		0.009	0.18	
	75.5	75.65	0.15		0.010	0.20	
	84.25	84.4	0.15		0.001	0.02	
	85.7	85.9	0.2		Tr.	----	
	86.35	86.5	0.15		0.001	0.02	
	95.5	95.9	0.4		0.001	0.02	
	98.4	98.5	0.1		0.003	0.06	
	99.5	99.7	0.2		0.004	0.08	
	100.3	100.5	0.2		0.001	0.02	
	102.8	102.9	0.1		0.003	0.06	
	104.6	104.7	0.1		0.002	0.04	
	107.0	107.5	0.5		0.001	0.02	
	131.9	132.3	0.4		0.012	0.24	
	144.6	145.1	0.5		0.009	0.18	
	145.1	145.5	0.4		0.014	0.28	
	145.5	146.5	1.0		0.002	0.04	
	146.5	146.8	0.3		0.011	0.22	
					0.009	0.18	
	153.2	153.4	0.2		0.006	0.12	
	193.7	193.9	0.2		0.006	0.12	
	197.05	197.20	0.15		0.004	0.08	
	213.25	213.6	0.35		0.005	0.10	
	221.9	222.2	0.3		0.001	0.02	

C-6-08							
	102.1	102.25	0.15		0.005	0.10	
	108.9	109.1	0.2		0.003	0.06	
	114.8	115.8	1.0		0.003	0.06	
	115.8	116.0	0.2		0.032	0.64	
	116.0	117.0	1.0		0.003	0.06	
	160.2	161.2	1.0		0.001	0.02	
	161.2	161.4	0.2		0.022	0.44	
	161.4	162.3	0.9		0.005	0.10	
	162.3	162.6	0.3		0.008	0.16	
	162.6	163.0	0.4		0.004	0.08	
	163.0	163.35	0.35		0.002	0.04	
	163.35	163.7	0.35		0.007	0.14	
	163.7	165.2	1.5		0.002	0.04	
	165.2	166.7	1.5		0.002	0.02	
	167.8	168.4	0.6		0.001	0.02	
	181.2	182.0	0.8		0.004	0.08	

C-7-08							
	39.4	39.6	0.2		0.005	0.10	
	40.2	40.6	0.4		0.006	0.12	
	40.6	41.2	0.6		0.014	0.28	
	89.6	91.6	2.0		0.002	0.04	
	91.6	92.6	1.0		0.007	0.14	
	92.6	93.0	0.4		0.003	0.06	
	93.0	94.1	1.1		0.001	0.02	
	94.1	94.3	0.2		Trace	---	
	95.3	95.5	0.2		0.001	0.02	
	100.7	101.5	0.8		0.003	0.06	
	102.6	104.1	1.5		Trace	----	
	107.3	108.8	1.5		0.001	0.02	
	110.6	112.2	1.5		trace		

C-8-08	From	To	Interval (m)		% U3O8	Lbs/ton	
	42.9	43.1	0.2		Trace	----	
	44.2	44.4	0.2		0.002	0.04	
	51.5	52.4	0.9		0.005	0.10	
	52.4	52.5	0.1		0.044	0.88	
	52.5	53.3	0.8		0.007	0.14	
	53.3	53.5	0.2		0.008	0.16	
	53.5	54.3	0.8		0.004	0.08	
	97.4	99.4	2.0		0.002	0.04	
	99.4	99.6	0.2		0.032	0.64	
	99.6	101.3	1.7		0.002	0.04	
	101.3	101.6	0.3		0.021	0.42	
	101.6	102.4	0.8		0.002	0.04	
	102.4	103.9	1.5		0.001	0.02	
	103.9	105.5	1.6		0.002	0.04	
	105.5	105.8	0.3		0.059	1.18	
	105.8	106.2	0.4		0.034	0.64	
	106.2	106.6	0.4		0.040	0.80	
	106.6	107.0	0.4		0.035	0.70	
	107.0	107.25	0.25		0.027	0.54	
	107.25	108.7	1.45		0.002	0.04	
	108.7	109.05	0.35		0.010	0.20	
	109.05	109.4	0.35		0.018	0.36	
	109.4	110.0	0.6		0.003	0.06	
	112.95	114.0	1.05		0.003	0.06	
	114.0	114.4	0.4		0.045	0.90	
	114.4	114.55	0.15		0.362	7.24	
	114.55	114.65	0.1		0.150	3.00	
	114.65	115.8	1.15		0.003	0.06	
	115.8	116.2	0.4		0.072	1.44	
	116.2	116.7	0.5		0.371	7.42	
	116.7	117.8	1.1		0.002	0.04	
	120.7	122.0	1.3		0.008	0.16	
	122.0	122.2	0.2		0.069	1.38	
	122.2	123.0	0.8		0.027	0.54	
	123.0	123.35	0.35		0.031	0.61	
	123.35	123.7	0.35		0.146	2.92	
	123.7	124.3	0.6		0.017	0.34	

	142.3	142.5	0.2		0.011	0.22	
	197.1	198.0	0.9		0.003	0.06	
	198.0	198.2	0.2		0.022	0.44	
	198.2	199.1	0.9		0.003	0.06	
	241.45	241.55	0.1		0.002	0.04	
	249.0	251.2	2.2		0.004	0.08	
	251.2	251.7	0.5		0.001	0.02	
	255.1	255.3	0.2		0.037	0.74	
	255.3	256.1	0.8		0.001	0.02	
	271.0	272.5	1.5		0.01	0.20	

Below are the four most significant intersections:

Section 1- from 51.5m to 54.3m (2.8 m)

Total of section interval x assay = 0.0193

Average assay = 0.007% U3O8 over 2.8 m (0.14 lbs/ton)

Section 2- from 97.4m to 110.0m (12.6 m)

Total of section interval x assay = 0.1078

Average assay = 0.009% U3O8 over 12.6 m (0.2 lbs/ton)

With higher grade section from 105.5m to 107.0m (1.5 m)

Average grade = 0.04% U3O8 or 0.8 lbs/ton

Section 3 -from 112.95m to 117.8 (4.85m)

Total of section interval x assay = 0.3393

Average assay = 0.07% U3O8 over 4.85m (1.4 lbs/ton)

Section 4 – from 120.7m to 124.3m (3.6m)

Total of section interval x assay = 0.1071

Average assay = 0.03% U3O8 over 3.6 m (0.6lbs/ton)

Two high grade sections

114.4 to 114.55 (0.15m) assaying 0.362% U3O8 (7.2 lbs/ton)

116.2 to 116.7 (0.50m) assaying 0.371% U3O8 (7.4 lbs/ton)

C-9-08							
	39.7	40.3	0.6		0.020	0.40	
	53.1	53.9	0.8		0.001	0.02	
	53.9	54.7	0.8		0.114	2.28	
	54.7	55.1	0.6		0.044	0.88	
	55.1	55.8	0.7		0.004	0.08	
	55.8	56.2	0.4		0.060	0.12	
	56.2	57.3	1.1		0.012	0.34	
	57.3	58.2	0.9		0.017	0.24	
	58.2	58.6	0.4		0.125	2.50	
	58.6	59.0	0.4		0.006	0.12	
	59.0	59.4	0.4		0.182	3.64	
	59.4	60.6	1.2		0.006	0.12	
	60.6	61.2	0.6		0.022	0.44	
	61.2	61.8	0.4		0.048	0.96	
	61.8	62.6	0.8		0.004	0.08	
	62.6	62.8	0.2		0.126	2.52	
	62.8	63.7	0.9		0.001	0.02	
	113.3	114.3	1.0		0.001	0.02	
	114.3	114.6	0.3		0.066	1.32	
	114.6	115.6	1.0		0.004	0.08	

Section from 53.1 m to 63.7 m (10.6 m)

Section x grade total = 0.3789

Average grade = 0.036% U3O8 or 0.72 lbs/ton

Four higher grade narrow sections

From 53.9 m to 54.7 m = 0.8 m assaying 0.114% U3O8 (2.28lbs/ton)

From 58.2 m to 58.6 m = 0.4 m assaying 0.125% U3O8 (2.50 lbs/ton)

From 59.0 m to 59.4 m = 0.4 m assaying 0.182% U3O8 (3.64 lbs/ton)

From 62.6 m to 62.8 m = 0.2 m assaying 0.126% U3O8 (2.52 lbs/ton)

C-12-08							
	31.2	32.4	1.2		0.003	0.06	
	35.0	35.7	0.7		0.007	0.14	
	35.7	36.7	1.0		0.048	0.96	
	36.7	37.6	0.9		0.082	1.64	
	37.6	38.2	0.6		0.001	0.02	
	38.2	39.0	0.8		0.001	0.02	
	39.0	39.9	0.9		0.001	0.02	
	45.3	45.9	0.3		0.001	0.02	
	45.9	46.2	0.6		0.006	0.12	
	46.2	46.5	0.3		0.173	3.46	
	46.5	47.1	0.6		0.007	0.14	
	47.1	47.5	0.4		0.027	0.54	
	47.5	48.6	1.1		0.001	0.02	
	50.9	51.1	0.2		0.018	0.36	
	53.9	54.8	0.9		0.001	0.02	
	58.8	60.3	1.5		Trace	---	
	67.7	69.0	1.3		0.001	0.02	
	74.4	76.6	2.2		0.001	0.02	
	79.9	81.0	1.1		0.002	0.04	
	84.5	85.9			Trace	---	
	94.0	95.6	1.6		0.001	0.02	
	124.3	125.2	0.9		Trace	---	
	156.3	157.6	1.3		0.004	0.08	
	160.7	162.0	1.3		0.002	0.04	
	202.6	203.5	0.9		0.006	0.12	
	203.5	204.4	0.9		0.037	0.74	
	204.4	205.2	0.8		0.089	1.78	
	205.2	206.5	1.3		0.010	0.20	

C-15-08							
	32.1	33.3	1.2		0.002	0.04	
	36.0	37.4	1.4		0.001	0.02	
	94.0	95.3	1.3		Trace	----	
	97.0	99.4	2.4		Trace	---	
C-16-08							
	95.8	97.0	1.2		Trace	---	
	106.8	107.4	0.6		0.001	0.02	
	108.2	109.3	1.1		0.003	0.06	
	110.5	112.3	1.8		Trace	---	
C-17-08							
	12.0	13.5	1.5		0.001	0.02	
	33.7	34.7	1.0		0.006	0.12	
	44.8	46.1	1.3		Trace	----	
	48.5	50.9	2.4		Trace	----	
	96.6	97.6	1.0		Trace	----	
	107.1	108.4	1.3		0.007	0.14	
	115.8	118.2	2.4		0.002	0.04	

C-18-08							
	33.0	34.2	1.2		0.002	0.04	
	34.9	36.5	1.6		0.002	0.04	
	38.2	40.2	2.0		Trace	---	
	58.2	59.2	1.0		0.001	---	
	67.3	69.0	1.7		Trace	---	
	71.5	72.3	0.8		Trace	---	
	80.0	80.5	0.5		Trace	---	
	83.5	84.8	1.3		Trace	---	
	88.5	89.4	0.9		0.001	0.02	
C-19-08							
	20.3	21.0	0.7		Trace	----	
	22.7	23.7	1.0		Trace	----	
	23.7	24.5	0.8				
	45.1	46.1	1.0		0.001	0.02	
	46.1	47.4	1.3		0.001	0.02	
	48.8	50.2	1.4		0.001	0.02	
	50.2	50.9	0.7		0.001		
	50.9	51.9	1.0		0.001	0.02	
	58.5	59.1	0.6		Trace		
	66.9	67.4	0.5		Trace		
	67.4	68.1	0.5		0.001	0.02	
	70.2	71.6	1.2		0.001	0.02	
	73.6	74.4	0.8		Trace		
	74.4	76.0	1.6		0.001	0.02	
	84.2	85.4	1.2		0.001	0.02	
	85.4	86.5	1.1		0.005	0.10	
	86.5	87.5	1.0		0.002	0.04	

C-20-08							
	10.8	12.2	1.4		Trace	----	
	12.2	13.0	0.8		Trace		
	13.0	13.7	0.7		Trace		
	13.7	15.1	1.4		Trace		
	15.1	16.0	0.9		0.001		
	16.0	17.8	1.8		0.001	0.02	
	17.8	18.5	0.7		Trace	----	
	18.5	19.2	0.7		Trace		
	19.2	19.6	0.4		0.001	0.02	
	23.9	24.2	0.3		0.001	0.02	
	24.2	25.8	1.6		0.001	0.02	
	25.8	26.7	0.9		0.001	0.02	
	26.7	27.3	0.6		0.004	0.08	
	27.3	28.0	0.7		0.004	0.08	
	40.9	43.9	4.0		0.001	0.02	
	43.9	44.6	0.7		Trace	----	
	44.6	45.5	0.9		0.001	----	
	45.5	46.8	1.3		Trace		
	46.8	47.6	0.8		0.001	0.02	
	47.6	48.7	1.1		0.001	0.02	
	49.2	50.4	1.2		0.001	0.02	
	50.4	51.2	0.9		0.001	0.02	
	51.2	52.0	0.8		0.003	0.06	
	52.0	53.3	1.3		0.002	0.04	
	53.3	54.7	1.4		0.002	0.04	
	54.7	55.5	0.8		0.001	0.02	
	55.8	56.3	0.8		Trace		
	56.3	57.1	0.8		Trace		
	57.1	58.1	1.0		Trace	----	
	58.1	59.1	1.0		0.001	0.02	
	59.1	60.4	1.3		0.002	0.04	
	60.4	61.0	0.6		0.004	0.08	
	61.0	61.9	0.9		0.001	0.02	
	61.9	62.6	0.7		0.001	0.02	
	62.6	63.4	0.8		0.002	0.04	
	63.4	63.9	0.5		0.002	0.04	
	67.9	69.7	1.8		Trace	----	
	69.7	70.3	0.6		0.001	0.02	
	70.3	70.9	0.6		0.002	0.04	
	70.9	71.7	0.8		0.001	0.02	
	71.7	72.4	0.7		Trace		

	72.4	73.2	0.8		0.001		
	73.2	73.9	0.7				
	73.9	74.8	0.9		Trace-w	-----	
	74.8	75.4	0.6		0.001	0.02	
	75.4	76.5	1.1		Trace	----	
	76.5	76.9	0.4		0.001	0.02	
	76.9	78.2	1.3		0.003	0.06	
	78.2	78.7	0.5		Trace	----	
	78.7	79.8	1.1		Trace		
	79.8	81.2	1.4		trace		
	81.2	82.7	1.5		Trace		
	83.6	84.5	0.9		0.001	0.02	
	84.5	85.1	0.6		Trace		
	85.1	86.2	1.1		0.001	0.02	
	86.2	87.3	1.1		0.001	0.01	
	87.3	87.9	0.6		Trace		
	87.9	88.6	0.7		Trace		
	88.6	89.4	0.8		Trace		
	89.4	90.5	1.1		Trace		
	90.5	91.6	1.1		Trace		
	91.6	92.3	0.7		0.001	0.02	
	92.3	93.6	1.3		0.001	0.02	
	93.6	94.1	0.5		0.001	0.02	
	94.1	94.6	0.5		0.006	0.12	
	94.6	95.4	0.8		0.003	0.06	
	95.4	96.6	1.2		0.001	0.02	
	96.6	97.5	0.9		Trace		
	97.5	98.4	0.9		0.002	0.04	
	98.4	99.7	1.3		Trace		
	99.7	101.2	1.5		0.001	0.02	
	101.2	101.9	0.7		Trace		
	101.9	102.7	0.8		Trace		